



# MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

## Hand Held and Gun Applied B3 Expanding Foam

### 1. Identification of the substance/preparation and the company/undertaking

#### 1.1 Identification of the substance or preparation

B3 PU Foam

#### 1.2 Use of the substance/preparation

Construction chemicals  
Assembly foam

#### 1.3 Company/undertaking preparation

JCP Construction Products  
Unit 14 Teddington Business Park  
Teddington, Middlesex TW11 9BQ  
Tel +44 208 943 1800  
Fax +44 208 943 1140

#### 1.4 Telephone number for emergencies

+44 208 943 1800 (0830 to 1700hrs Monday to Friday)

#### 1.5 email

[jcpenquiries@owlett-jaton.com](mailto:jcpenquiries@owlett-jaton.com)

### 2. Hazards identification

#### Hazard description



Xn Harmful  
F+ Extremely flammable

Combustible gas, heavier than air; can accumulate on flat surfaces and in lower parts of rooms.

Foam sticks easily to the skin and other surfaces.

The product is labelled as laid down in the latest version of the "General Classification Guidelines for Preparations in the EU"

Warning! Pressurized container

R20 Harmful by inhalation

R36/37/38 Irritating to eyes, respiratory system and skin.

R40 Limited evidence of carcinogenic effect

R42/43 May cause sensitisation by inhalation and skin contact

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

R53 May cause long term adverse effects in the aquatic environment

Contains isocyanates. See information supplied by manufacturer.

May cause harm to breastfeeding babies

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used in areas of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to EN14387) is used.

Keep away from sources of ignition - No Smoking

Do not spray on a naked flame or incandescent material

Keep out of reach of children.

The classification is in line with current EC lists. It is extended by information from technical literature and company information.

Classification of the preparation in respect of phrase R53, taking into account the content of C14-C17 chlorinated alkanes, was made on the basis of acute toxicology tests performed on daphnia Daphnia magna and algae report BMG study no. A10-00856 and BMG study no. A10-00857



# MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

## Hand Held and Gun Applied B3 Expanding Foam

### 3. Composition/information on ingredients

Hazardous Ingredients	CAS No. EINECS No.	Conc. In %	Hazard symbol	Risks (R-phrases)
polymethylene polyphenyl polyisocyanate, isomers and homologues	9016-87-9	30.0-60.0	Xn, Xi	20-36/37/38-40-42/43-48/20
tris(2-chlorisopropyl)-phosphate	13674-84-5	<25.0	Xn	22
alkanes, C14-17, chloro	855535-85-9 287-477-0	<20.0	N	50/53-64-66
propane	74-98-6 200-827-9	<15.0	F+	12
butane	106-97-8 203-448-7	<15.0	F+	12
isobutane	75-28-5 200-857-2	<15.0	F+	12
dimethyl ether	115-10-6 204-065-8	,10	F+	12

**Additional information:** For the wording of the listed risk phrases refer to section 16

### 4. First aid measures

#### 4.1 After inhalation

Supply fresh air. If required, provide rescue breaths. Keep patient warm. Consult doctor if symptoms persist.

#### 4.2 After skin contact

Remove uncured foam using lint free cloth and an unaggressive solvent, e.g. ethanol. Wash hands and cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned

#### 4.3 After eye contact

Rinse open eye for several minutes under running water and consult a doctor.

#### 4.4 After swallowing

Do not induce vomiting. Seek medical help immediately  
Rinse out mouth and drink plenty of water.

### 5. Fire-fighting measures

#### 5.1 Suitable extinguishing media

Quantities of water  
Polyvalent foam  
BC powder  
Carbon dioxide

#### 5.2 Unsuitable extinguishing media

None

#### 5.3 Special hazards caused by the substance, its products of combustion or resulting gases

Can form explosive gas-air mixtures  
Formation of toxic gases is possible during heating or in case of fire.

#### 5.4 Protective equipment

Wear self-contained breathing apparatus  
Wear full protective suit



# MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

## Hand Held and Gun Applied B3 Expanding Foam

### 6. Accidental release measures

#### 6.1 Personal protection/precautions

Keep away from ignition sources  
Wear protective clothing  
Do not breath gas, fumes, spray, vapour  
Ensure adequate ventilation

#### 6.2 Environmental precautions

Do not allow to enter sewers, surface or ground water.

#### 6.3 Method of collecting/clean up

Allow product to solidify and remove by mechanical means  
Remove uncured foam with acetone  
Dispose of contaminated waste as per section 13  
Ensure adequate ventilation

#### 6.4 Additional information

See section 13 for disposal information

### 7. Handling and storage

#### 7.1 Handling

Observe very strict hygiene - avoid contact  
Do not activate the can if temperature is above 25°C.  
Ensure good ventilation/exhaust at the workplace  
Open and handle containers with care

#### 7.2 Information about fire/explosion protection

Pressurized container: protect from sunlight and do not expose to temperatures above 50°C  
Do not pierce or burn, even after use.  
Do not spray onto naked flame or incandescent material  
Keep away from ignition sources. Do not smoke  
Protect against electrostatic charges.

#### 7.3 Storage

Keep out of direct sunlight  
Store in a cool area  
Store in a dry area  
Keep away from heat sources, ignition sources, acids, bases  
Store away from foodstuffs  
Store in vertical position in original container.  
Protect from frost  
Store under lock and key and out of reach of children

<b>Storage temperature</b>	+5 to +30 °C
<b>Quantity limit</b>	N.D. kg
<b>Storage life</b>	365 days
<b>Material for packaging</b>	Original container

### 8. Exposure controls / Personal protection

#### Ingredients with limit values that require monitoring at the workplace

##### 9016-87-9 polymethylene polyphenyl polyisocyanate, isomers and homologues

WEL	Short term value	0.07 mg/m <sup>3</sup>
	Long term value	0.02 mg/m <sup>3</sup>
	Sen; as-NCO	

##### 106-97-8 butane

WEL	Short term value	1810 mg/m <sup>3</sup> , 750ppm
	Long term value	1450 mg/m <sup>3</sup> , 600ppm
	Carc (if more than 0.1% of buta 1,3-diene	

<b>115-10-6</b>	Short term value	958 mg/m <sup>3</sup> , 500ppm
	Long term value	766 mg/m <sup>3</sup> , 400ppm



## MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

### Hand Held and Gun Applied B3 Expanding Foam

#### Personal protective equipment

##### General protective and hygiene measures

Keep away from food, drinks and animal feed  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at end of work  
Avoid contact with skin and eyes

##### Respiratory protection

In case of brief exposure or low level pollution use respiratory filter device. In case of intensive or long exposure use self contained breathing apparatus.

##### Hand protection



Wear protective gloves

##### Material of gloves

PVC or Rubber gloves of suitable quality as defined by the glove manufacturer

##### Eye protection



Wear tight sealed goggles

##### Protective clothing

Protective work clothing

## 9. Physical and chemical properties

<b>Description</b>	Rapidly curing foam dispensed by gas propellant from an aerosol container
<b>Colour</b>	Light yellow
<b>Odour</b>	Characteristic
<b>Melting point/range</b>	Undetermined
<b>Boiling point/range</b>	Not applicable as aerosol
<b>Flash point</b>	<0°C (propellant)
<b>Danger of explosion</b>	Heating may cause explosion
<b>Explosion Limits</b>	Lower 1.5 Vol%      Upper 11.0%Vol
<b>Vapour pressure</b>	>500kPa (in the container)      <1*10 <sup>-5</sup> mmHg w 25°C (MDI)
<b>Density at 20°C</b>	≤ 1.3 (PMDI) g/cm <sup>3</sup>
<b>Solubility in Water</b>	Insoluble
<b>Miscibility with water</b>	Reacts with water

## 10. Stability and reactivity

##### Thermal decomposition / conditions to be avoided

No decomposition if used and stored according to specifications

##### Materials to be avoided

Reacts strongly with water and other substances containing an active hydrogen atom

##### Dangerous reactions

No dangerous reactions known

##### Dangerous decomposition products

No dangerous decomposition products known



## MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

### Hand Held and Gun Applied B3 Expanding Foam

#### 11. Toxicological information

##### Acute toxicity

##### LD/LC50 values relevant for classification

##### 13674-84-5 tris(2-chlorisopropyl)-phosphate

Oral LD50 >2000 mg/kg (rat)  
Dermal LD50 >2000 mg/kg (rat)  
Inhalation LC50/4h >0.05 mg/l (rat)

##### 101-68-8 4,4' methylenediphenyl diisocyanate

Oral LD50 >9200 mg/kg (rat)  
Inhalation LC50/4h >178 mg/l (rat)

##### Primary irritant effect:

**On the skin** irritant to skin and mucous membrane

**On the eye** irritating effect

**Sensitisation** sensitisation possible through inhalation  
sensitisation possible through skin contact

##### Additional toxicological information

Harmful  
Irritant

#### 12. Ecological information

##### Information about elimination (Persistence and degradability)

Not biodegradable

**Mobility and bioaccumulation potential** Does not accumulate in organisms

##### Ecotoxicological effects

##### Aquatic toxicity

##### 13674-84-5 tris(-chlorisopropyl)-phosphate

EC50 47mg/kg (alg)

##### 85535-85-9 alkanes, C14-17, chloro

EC50 >1000mg/l/48h (daphnia)  
>1000mg/l/72h (alg)

NOEC <1000mg/l (alg)

##### Additional ecological information

##### General notes

Do not allow undiluted product or large quantities of it to reach ground water, water courses or sewage systems

#### 13. Disposal considerations

##### Recommendation

Must not be disposed of with household waste. Do not allow product to reach sewage system.

##### European Waste Catalogue

07 02 08\* other still bottoms and reaction residues

07 02 13 waste plastic

15 01 05 composite packaging

Uncleaned packaging

**Recommendation:** Disposal must be made according to official regulations



# MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

## Hand Held and Gun Applied B3 Expanding Foam

### 14. Transport information

#### Land transport ADR/RID (cross border)

ADR/RID class	2 5F Gases
Danger code (Kemler)	-
UN Number	1950
Packaging group	-
Hazard label	2.1
Remarks	Exemption from ADR provisions by LQ principal (rule 3.4.5) Inner packaging, max 1 litre on capacity; outer packaging - max gross weight 30kg Inner packaging, max 1 litre on capacity; based on common ground and covered in shrink fill - max gross weight 20kg

#### Maritime transport IMDG

IMDG class	2 5F
UN number	1950
Label	2.1
Packaging group	-
EMS number	F-D,S-U
Marine pollutant	Yes
Proper shipping name	Aerosol

#### Air transport ICAO-TI and IATA-DGR

ICAO/IATA Class	2 5F
UN/ID number	1950
Label	2.1
Proper shipping name	Aerosol

### 15. Regulatory information

#### Labelling according to EU Guidelines:

The product has been classified and marked in accordance with EU directives/ Ordinance of Hazardous Materials

#### Code letter and hazard designation of product



Xn Harmful  
F+ Extremely flammable

#### Hazards-determining components of labelling

polymethylene polyphenyl polyisocyanate, isomers and homologues

#### Risk phrases

20	Harmful by inhalation
36/37/38	Irritating to eyes, respiratory system and skin
40	Limited evidence of carcinogenic effect
42/43	May cause sensitisation by inhalation and skin contact
48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
53	May cause long-term adverse effects in the aquatic environment

#### Safety phrases

23	Do not breath gas/fumes/vapour/spray
36/37/38	Wear suitable protective clothing, gloves and eye/face protection
45	In case of accident or if you feel unwell seek medical advice immediately (Show the label where possible)
51	Use only in well ventilated area
61	Avoid release to the environment. Refer to special instructions/safety data sheet
63	In case of accident by inhalation; remove casualty to fresh air and keep at rest.



## MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex II

### Hand Held and Gun Applied B3 Expanding Foam

#### Special labelling of certain preparations

Contains isocyanides. See information supplied by the manufacturer

May cause harm to breastfed babies

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product  
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

keep away from sources of ignition - No smoking

Do not spray on a naked flame of incandescent material

Keep out of reach of children

#### 16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legal valid contractual relationship.

#### Relevant R-phrases

- |          |                                                                                                 |
|----------|-------------------------------------------------------------------------------------------------|
| 12       | Extremely flammable                                                                             |
| 20       | Harmful by inhalation                                                                           |
| 22       | Harmful if swallowed                                                                            |
| 23/37/38 | Irritating to eyes, respiratory system and skin                                                 |
| 40       | Limited evidence of carcinogenic effect                                                         |
| 42/43    | May cause sensitisation by inhalation and skin contact                                          |
| 48/20    | Harmful: danger of serious damage to health by prolonged exposure through inhalation            |
| 50/53    | Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment |
| 64       | May cause harm to breastfed babies                                                              |
| 66       | Repeated exposure may cause skin dryness or cracking                                            |

#### Recommended restrictions of use

Sealing and mounting of construction elements

Mounting of doors and windows cannot be performed without the use of mechanical connectors.  
Before use, naturally bring the can up to room temperature. Shake the container well. Screw on the nozzle or screw can onto applicator gun. Work from the bottom of a void towards the top. Control the spray volume by adjusting the pressure on the can nozzle or gun trigger. After release from container the foam increases in volume. Use special cleaner to remove uncured foam. Cured foam can only be removed mechanically. After full cure protect the foam against UV radiation. In lower temperatures the foam expands and cures slower. The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfil safety requirements and not to guarantee its specific properties.

In cases where application conditions are not subject to the manufacturers control, the safe product use and complying with regulations is the responsibility of the user.